



Item	Input Voltage	Output Voltage	Input current	Power	Convert efficiency	PF	Dimension (MM)	Application	SAA	CE	FC
HPI-24W01-VXX	AC100-240V	DC30-45V	300mA	9-15W	89%	0.95	160*18*10	Isolated Driver for T8/T10			
	AC100-240V	DC30-45V	420mA	15-20W	89%	0.95	160*18*10	Isolated Driver for T8/T10			
	AC100-240V	DC30-45V	500mA	15-22W	89%	0.95	160*18*10	Isolated Driver for T8/T10			
	AC100-240V	DC30-45V	600mA	18-24W	89%	0.95	160*18*10	Isolated Driver for T8/T10			
HPI-24W02-VXX	AC100-240V	DC30-45V	300mA	9-15W	89%	0.95	280*18*10	TUV approved driver, For T8 T10			
	AC100-240V	DC30-45V	420mA	15-20W	89%	0.95	280*18*10	TUV approved driver, For T8 T10			
	AC100-240V	DC9-45V	500mA	15-22W	89%	0.95	280*18*10	TUV approved driver, For T8 T10			
	AC100-240V	DC9-45V	600mA	18-24W	89%	0.95	280*18*10	TUV approved driver, For T8 T10			
HPE-15W-VXX	AC100-240V	DC9-45V	300mA	3-15W	87%	0.92	88*45*27	CE approved external driver for ceiling light downlight and so on			
	AC100-240V	DC9-45V	500mA	10-20W	87%	0.92	88*45*27	CE approved external driver for ceiling light downlight and so on			
	AC100-240V	DC9-45V	700mA	15-25W	87%	0.92	88*45*27	CE approved external driver for ceiling light downlight and so on			
	AC100-240V	DC9-45V	800mA	25-30W	87%	0.92	88*45*27	CE approved external driver for ceiling light downlight and so on			
HPE-30W-VXX	AC100-240V	DC25-45V	300mA	10-15W	87%	0.92	130*45*27	SAA approved external driver for downlight,panel light and so on			
	AC100-240V	DC25-45V	500mA	15-20W	87%	0.92	130*45*27	SAA approved external driver for downlight,panel light and so on			
	AC100-240V	DC25-45V	700mA	20-30W	87%	0.92	130*45*27	SAA approved external driver for downlight,panel light and so on			
	AC100-240V	DC25-45V	900mA	30-36W	87%	0.92	130*45*27	SAA approved external driver for downlight,panel light and so on			

HPE-50W-VXX	AC100-240V	DC30-45V	1000mA	30-55W	87%	0.92	160*42*35	CE approved external driver for wall washer,high bay light and so on	
	AC100-240V	DC30-45V	1200mA	30-55W	87%	0.92	160*42*35	CE approved external driver for wall washer,high bay light and so on	
	AC100-240V	DC30-45V	1400mA	30-55W	87%	0.92	160*42*35	CE approved external driver for wall washer,high bay light and so on	
HPI-32W-VXX	AC100-240V	DC30-45V	600mA-700mA	18-32W	89%	0.92	310*18*10	TUV approved driver, For T8 T10	

**Note:**1.CE、TUV,SAA,C-tick,PSE approved;

2 .Use chip imported from USA, Strong anti-jamming ability, Extremely reliable;

3.Wide input voltage (90-264Vav) ;

4.High PF, 230V 18W can be over 95%;

5.Full range for output specification, 100-1500mA all are mass production product;

6.Exact output current, inspection below 3%, mass production below 5%,keep stable even long time use;

7.High efficiency18W >89%, a little different in different power;

8.Wide range operation in temperature, -40 to 60 degree Celsius;

9.Long life , high temperature aging 4000H, >40000H in Theory;

10.ON/OFF long life, both in high temperature high voltage、low temperature low temperature up to 20000 times;

11.Very safe, High voltage 3750V, Leakage current below 2mA